

# 705 PO

## Elasticity and Flexibility Modifier

**Supplied in shape of:**

Mixture, Pellets.

**Active agent:**

Polyolefin plastomer.

**Area of use:**

**HECO**<sup>®</sup>ELAST 705 PO is suitable for processing polyolefins such as polyethylene and polypropylene in injection moulding, extrusion and extrusion blow moulding.

**Recommended dose:**

**HECO**<sup>®</sup>ELAST 705 PO is added in the range of 5.0 - 25.0 % depending on the desired properties.

**Properties:**

**HECO**<sup>®</sup>ELAST 705 PO significantly improves the elasticity and flexibility of polyolefins. In addition, it also improves the flow properties and transparency.

**Gebindegröße:**

1.375,0 kg (55 Sack à 25,0 kg) / Palette, netto.

**Safety Precautions**

**Foodstuff regulation:**

Approval according to EU (Regulation) No. 10/2011.

Approval according to the US FDA, see "Food Contact Approvals".

**Storage:**

No reduction in quality has been reported when properly stored under normal room conditions up to twelve (12) months.

**Handling:**

The precautions and hygienic measures usual in the handling of any chemical product should be observed.

**In case of fire:**

In case of fire, suitable extinguishers are aqueous spray, foam or dry chemical; a full jet of water is unsuitable.

**HECOPLAST**<sup>®</sup> and **HECO**<sup>®</sup> are registered trademarks

Our information is based on the most careful analysis, nevertheless these are not guaranteed product features.  
Specific field tests are being recommended under any circumstance.

**HECOPLAST**<sup>®</sup> GmbH Kunststoffadditive, Bremke 17, D - 58638 Iserlohn Telephone + 49 2371 / 797 61-0 – E-Mail: info@hecoplast.de