

707 PO

Soft-Touch- and Elasticity Modifier

Supplied in shape of:

Mixture, Pellets.

Active agent:

Thermoplastic polyolefin.

Area of use:

HECO[®]ELAST 707 PO is a thermoplastic polyolefin typically used for coextruded cast films and injection moulding applications.

Recommended dose:

HECO[®]ELAST 707 PO is added in the range of 1.0 - 30.0 % depending on the desired properties.

Properties:

HECO[®]ELAST 707 PO features high softness, low modulus, high gloss and excellent clarity. It can be blended with other trans-parent polyolefin resins to improve impact strength at low temperatures and maintain film transparency. It is also suitable for injection moulding applications where high transparency and good gloss combined with good flexibility are required, such as household goods and toys.

Pallet size:

1.375.0 kg (55 sacks at 25.0 kg) / pallet, net.

Safety Precautions

Foodstuff regulation:

Approval according to EU (VO) No. 10/2011. This product contains one or more components with a specific migration limit.
Approval according to the US FDA, see "Food Contact Approvals".

Storage:

No reduction in quality has been reported when properly stored under normal room conditions up to twelve (12) months.

Handling:

The precautions and hygienic measures usual in the handling of any chemical product should be observed.

In case of fire:

In case of fire, suitable extinguishers are aqueous spray, foam or dry chemical; a full jet of water is unsuitable.

HECOPLAST[®] and **HECO**[®] are registered trademarks

Our information is based on the most careful analysis, nevertheless these are not guaranteed product features.
Specific field tests are being recommended under any circumstance.

HECOPLAST[®] GmbH Kunststoffadditive, Bremke 17, D - 58638 Iserlohn Telephone + 49 2371 / 797 61-0 – E-Mail: info@hecoplast.de