

101 PE

Non-migrating Slip Agent

Supplied in shape of:

Mixture, Flakes.

Active agent:

Non-migrating slip and demoulding additive.

Area of use:

HECO[®]SLIP 101 PE is suitable for processing polyethylene, polypropylene and polyamide in injection moulding and extrusion.

Recommended dose:

HECO[®]SLIP 101 PE is added in the range of 1.0 – 5.0 % depending on the desired properties. We recommend an addition of min. 1.0 – 2.0 %.

Properties:

HECO[®]SLIP 101 PE is a non-migrating internal slip agent and increases the flow ability of the polymer melt. This facilitates the mould filling and demoulding properties.

Pallet size:

1000.0 kg (50 Sack á 20.0 kg) / Pallet, net.

Safety Precautions

Foodstuff regulation:

Approval according to EU (VO) No. 10/2011.

Approval according to the US FDA, see "Food Contact Approvals".

Storage:

No reduction in quality has been reported when properly stored under normal room conditions up to twelve (12) months.

Handling:

The precautions and hygienic measures usual in the handling of any chemical product should be observed.

In case of fire:

In case of fire, suitable extinguishers are aqueous spray, foam or dry chemical; a full jet of water is unsuitable.

HECOPLAST[®] and **HECO**[®] are registered trademarks

Our information is based on the most careful analysis, nevertheless these are not guaranteed product features.
Specific field tests are being recommended under any circumstance.

HECOPLAST[®] GmbH Kunststoffadditive, Bremke 17, D - 58638 Iserlohn Telephone + 49 2371 / 797 61-0 – E-Mail: info@hecoplast.de